

JCB SUPER LOADER - **ONE MACHINE, MULTIPLE SOLUTIONS**



JCB SUPER LOADER | 2DXL-3I, 2DXL-40

Gross power: 36.4kW (49hp), Operating weight: 5600kg



Why Super Loader?



Super Performance

New long loader arm - High dump height options of 3.1 / 4.0 m.



Super Reliability

Torque converter, JCB transmission and parallel lift loader arm for higher uptime.



Super Efficiency

Ease of operation, lower maintenance & effective performance.



Super Versatility

10+ Attachments eg. 1.3 cum shovel, cotton bucket, high dump shovel & bale grabber.



Super Operator Comfort

Cabin/Canopy with front glass & comfortable seat for ease of operation.



Super Technology with Safety

LiveLink:*

An advanced telematics monitoring system based on principles of service, operation and security to manage your machine remotely.



Super Product Support

Widespread 700+ dealer outlets network to get best after-sale services.



*Optional

IDEAL MACHINE FOR COTTON INDUSTRY

Rear cooling pack to avoid over-heating

- Reduces radiator clogging in extreme dusty conditions (cotton, mushroom or coir)
- Better cooling of machine
- No chance of accidental fire

Front mesh

- Prevents radiator clogging
- Easy to clean radiator

Heat insulation shield

- Insulation kit consists of a manifold cover, muffler & end cap to avoid fire
- Safety of the machine round the clock



SUPER RELIABILITY

Robust structure

- Structural integrity achieved through rigorous design involving F.E.A and strain gauging
- JCB manufacturing process & testing ensure consistent quality & reliability of structures
- Robust and heavy duty structure made of high quality steel

Durable and reliable JCB Transmission

- JCB synchroshuttle provides superb driving power in all conditions
- Consists of 4 speed, fully synchromesh, smooth shift gear box with integral torque convertor
- Torque convertor stall ratio is 3.01:1



SUPER OPERATOR COMFORT

Today, working at a construction site is a real challenge. It requires hard work in all weather conditions. In a world where the construction industry has to evolve every day to meet the ever-increasing demands and deliver in tight deadlines, JCB Super Loader Machine stays updated to the changing industry dynamics and enhances the safety & comfort of the operators. Well protected with tough front glass and a comfortable seat, the JCB Super Loader Machine has a cabin/canopy that ensures the operator gets complete comfort, safety and ease to deliver enhanced performance and beat all challenges at any site with ease and super control.

JCB Super Loader's Features

- Canopy as standard
- Cabin (optional) more comfortable
- Front Glass - more safety
- Reverse Shuttle Gear - ease of operation
- Comfortable wider set



SUPER PERFORMANCE IN 4 WHEEL DRIVE

Higher traction and better mobility

- Provides higher traction on all four wheels
- Allows excellent mobility even on slush and sand
- Enables machine to overcome gradient easily even while loading
- Available as an option



Powerful engine

- 1 Highly fuel efficient & powerful water cooled diesel engine developing 36.4 kW (49 hp) @ 2200 RPM
- 2 Water separator provided for more reliability and longer fuel pump life
- 3 Long service intervals (500 hours) for achieving better economy



Incredible productivity

- 1 The 258l PSI hydraulic system pressure allows higher break out forces enabling the machine to penetrate for higher productivity
- 2 Durable loader arm design for higher lift capacity and lower cycle times
- 3 28 Km/hr travel speed for faster coverage of longer distance and on site movements



ONE MACHINE, MULTIPLE SOLUTIONS



General purpose shovel




6 in 1 Shovel



High dump shovel



Grabbing fork shovel



High dump high volume shovel



Coal handling



Loose wood




Grabber



Pallet handling



Dozer levelling




1.3 cum shovel (low density)



Front end dozer blade



Bagasse dozer



Pallet fork



Bale grabber



Reliability & Safety

- Front glass
- Durable counterweight
- Torque convertor
- Sturdy axles



Easy finance & Machine registration (RTO)

- Attractive and easy finance scheme available
- Easy registration at all RTOs across India
- Insurance of complete machine



Value for money

- Excellent resale value
- Single invoice of machine+ attachment, thus, convenient EMI
- Single warranty support system



Serviceability

- 700+ Dealer outlets network
- Genuine parts availability
- 24x7 Customer care call centre



Operator comfort

- Full cover canopy
- Spacious cabin
- Comfortable operator seat
- Easy gear shifting (forward / reverse)



LiveLink : Advanced telematics system

Service

- Service reminder
- Machine data backup
- Critical machine health alerts

Operation

- Fuel level information
- Machine utilisation reports
- Engine status

Security

- GPS tracking
- Operating hours
- Possible intrusion / Tow away
- Geofencing



JCB SUPER LOADER

ONE MACHINE, MULTIPLE SOLUTIONS





EXCEEDING EXPECTATIONS
EVERYWHERE

Towards Industry's finest customer support network



5,000⁺
Trained service
engineers



18
Training centres



3,000⁺
Mobile service
engineers



250⁺
Mobiles vans



24x7
Support
12 Languages



60⁺
Dealers



700⁺
Outlets



5
Parts warehouses



PEACE OF MIND

JCB'S CERTIFIED ENGINEERS FOR SUPER LOADER

JCB's certified engineers are there to maximise your profitability and reduce downtime. Our engineers are always there to serve the customers and provide value-added solutions to all their concerns regarding the machines and services.



JCB trained and certified engineers



Best-in-class service and repairs



On-site training and support



SMART & DIGITAL SUPPORT



Download from:



LiveLink



Genuine Parts

Scan the QR Code to connect to JCB Support Facebook Page



EXTENDED CARE

GIVE YOUR MACHINE EXTENDED WARRANTY AND CARE.

- JCB Careplus is an extended warranty programme that comes into effect after the machine standard warranty expires.
- JCB Careplus can be purchased within the 1st year from the sale of the machine.
- The programme offers you peace of mind and saves your maintenance cost even after your machine standard warranty expires.



Extended
Warranty
Programme

BENEFITS OF JCB CAREPLUS



No limits
on number
of claims



Preventive
maintenance
service*



Nationwide
coverage*



JCB skilled
manpower
support



Maximum
productivity



Maximum
uptime



Maximum
performance



Breakdown
cost protection



Better resale
value




*T&C Apply



PERFORMANCE DIMENSIONS



STATIC DIMENSIONS



LOADER PERFORMANCE

			2DXL-31	2DXL-40
M	Dump height	m (ft-in)	3.10 (10-2)	4.0 (13-1)
N	Load over height	m (ft-in)	3.55 (11-8)	4.15 (13-7)
O	Pin height	m (ft-in)	3.71 (12-2)	3.71 (12-2)
P	Pin forward reach	m (ft-in)	0.27 (0-11)	0.27 (0-11)
Q	Reach at ground	m (ft-in)	1.88 (6-2)	2.00 (6-7)
R	Max reach at full height	m (ft-in)	1.04 (3-5)	1.20 (3-11)
S	Reach at full height - shovel dumped	m (ft-in)	0.73 (2-5)	0.90 (2-11)
T	Below ground level depth	m (ft-in)	0.105 (0-4)	0.152 (0-6)
U	Rollback at ground	deg	41	42
V	Dump angle	deg	43	42
	Payload	kgf	1000	900
	Shovel break-out force	kgf	3480	3480
	Loader arm break-out force	kgf	1700	1700
	Standard shovel	cu.m	0.60 (G.P. Shovel)	0.62 (Hi Dump)

Benefits of using JCB Super Loader

Productivity & reliability

Given the high quality machine that it is, it offers high productivity and reliability with torque convertor

Easy to operate

The Super Loader is easy to operate and manoeuvre in constraint spaces

Versatility

A wide array of attachments such as high dump shovel, 6-in-1 shovel, dozer blade make the machine highly versatile

Safety & comfort

Enabled with added safety features, JCB 2DXL Super Loader offers enhanced security and operator comfort

Style & design

It is designed for better visibility and comes with an open canopy or fully closed cabin, making it more stylish & comfortable

Easy finance & registration

Attractive and easy finance schemes are made available by many financiers for the purchase of JCB Super Loader. It can easily be registered at all RTO's across India

STATIC DIMENSIONS

			2DXL-31	2DXL-40
A	Overall length	m (ft-in)	5.90 (19-4) (standard shovel)	6.1 (20-0)
B	Wheelbase	m (ft-in)	2.08 (6-10)	2.08 (6-10)
C	Rear overhang	m (ft-in)	1.48 (4-6)	1.48 (4-6)
D	Minimum ground clearance	m (ft-in)	0.33 (1-1)	0.33 (1-1)
	Overall width	m (ft-in)	1.85 (6-1)	1.85 (6-1)
G	Height to top of cab	m (ft-in)	2.66 (8-8)	2.66 (8-8)
J	Track width - Rear	m (ft-in)	1.42 (4-8)	1.42 (4-8)
K	Track width - Front	m (ft-in)	1.58 (5-2)	1.58 (5-2)
L	Width over shovel	m (ft-in)	1.93 (6-4)	1.93 (6-4)



ENGINE

KOEL 4R810, naturally aspirated, 4 cylinder, water cooled, BS-III diesel engine.

Displacement : 3.2 L

Gross power : 36.4 kW (49 hp)

Gross torque : 203 Nm (20.7 kgm) @ 1300 rpm

TRANSMISSION

The JCB SS 700 synchroshuttle transmission consists of a 4-speed, fully synchromesh, smooth shift gearbox with integral torque convertor and electrically operated reversing shuttle.

- Easy to use, column mounted **electric reversing shuttle** switch can change machine direction while allowing operator to keep hands on the steering wheel leading to fast cycle time
- The pedals layout and conventional 4-pattern gear level with transmission switch add to the overall ease of operation.
- Torque converter stall ratio 3.01:1

AXLES

Front Axle:
2WD steer axle, centrally pivoted with oscillation angle of 16°

Rear Axle:
Drive axle rigidly mounted incorporates JCB Max-track torque proportioning differential, driven by prop shaft from gear box.

BRAKES

Service : Hydraulically actuated, dual line, self-adjusting (compensated), oil immersed, multi-disc type on the rear axle, well protected from dirt, water, etc. Operated through independent pedals linked together for normal use. Two independently operating foot pedals enable machine to maneuver in tight spaces.

Parking : Hand operated disc brakes on rear axle input disc.

STEERING

Full power, front wheel hydrostatic power steering with manual capability in the event of engine or hydraulic power failure.

- Max. steering angle: $\pm 43^\circ$

ELECTRIC

100 Ampere-hour 12 Volts battery system with alternator and full road lighting.

TYRES

Front	:	8.25 X 16
Rear	:	14.9 X 24 (Industrial Tyre Pattern Tyres) & 12.0 X 24 (Heavy Duty Tyres)
Front tyre pressure	:	80 PSI (8.25 X 16)
Rear tyre pressure	:	31 PSI (14.9 X 24) 44 PSI (12.0 X 24)

SPEED (2WD)

Gear	Forward	Reverse
1st	4.4	4.4
2nd	7.1	7.1
3rd	15.2	Not recommended
4th	28.8	Not recommended


TURNING CIRCLE

Inner wheels brake

A Outside loader bucket	11.34 m	11.5 m
B Outside wheels	8.0 m	8.0 m

Inner wheels not brake

A Outside loader bucket	11.80 m	11.96 m
B Outside wheels	8.72 m	8.72 m



*Standard bucket in travel position

HYDRAULICS

- Pump type : 2 Section displacement gear.
- Pump flow : 63 lpm
- Main relief valve : 178 bar (258 PSI)

SERVICE CAPACITY

Fuel tank	:	60 L
Hydraulic tank	:	60 L
Engine coolant	:	13.5 L
Engine oil	:	8.0 L
Transmission	:	16 L
Rear axle	:	21 L

CANOPY/CABIN

- Front glass with wiper provided for operator comfort while driving.
- Excellent operator safety
- Floor mat and plenty of leg room minimise fatigue and provide extra comfort to operators.
- Adjustable operator seat combined with ergonomically positioned controls and soft touch steering wheel allow an operator to work un-interruptedly for long hours.
- CANOPY provides easy 'walk through' access. Other features include seat belt, large convex rear view mirror, front screen wiper, front and rear horn, hazard warning system, lockable tool box and helper seats (2+1).
- Instrument panel is positioned on the right hand side and includes engine speed, engine hours, fuel level, water temperature and mobile charger.
- Audible and visual fault warning system for alternator charging, coolant temperature, engine oil pressure, blocked air filter, transmission oil pressure and temperature and hand-brake on.

WEIGHT

Shipping weight (3.1 m with : 5600 kg
standard bucket & Cab)

ATTACHMENTS

- Booster shovel (High dump shovel for 4.0 m dump height)
- 6-in-1 shovel
- High dump high volume shovel
- Front end dozer blade
- Bagasse dozer
- Grabbing fork shovel
- Pallet fork
- Bale grabber
- 1.3 cum shovel (low density)

LIVELINK

Advanced telematics system enables you to monitor and manage your machines remotely by providing information on:

Service : Routine maintenance information and alerts.

Operation : Health alerts and usage data.

Security : Machine location & movement data.

OPTION

- Heavy-duty rear tyres (12 x 24)
- Cabin
- LiveLink
- RCP (Rear Cooling pack for applications like Cotton, Coir, etc.)
- 4WD



ONE COMPANY, OVER 300 VARIANTS.

Dealer's stamp:

JCB INDIA LIMITED 23/7 Mathura Road, Ballabgarh - 121 004 Haryana, India. Fax: 91 129 2309050

For more information SMS "**JCB**" to **56767** or call our toll free no. **1800-1037-386**

Website: www.jcb.com

Follow us: [f](#) [t](#) [v](#) [i](#) [in](#) /JCBIndiaLtd

©2009 JCB Sales. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any other means, electronic, mechanical, photocopying or otherwise, without prior permission from JCB Sales. All references in this publication to operating weights, sizes, capacities and other performance measurements are provided for guidance only and may vary dependant upon the exact specification of machine. They should not therefore be relied upon in relation to suitability for a particular application. Guidance and advice should always be sought from your JCB Dealer. JCB reserves the right to change specifications without notice. Illustrations and specifications shown may include optional equipment and accessories. The JCB logo is a registered trademark of J C Bamford Excavators Ltd.

